
## THE ONLY PATENTED\* **STORAGE SYSTEM** THAT **DOES NOT MODIFY** THE INSTALLATION.






SOLAR ECLIPSE designed, patented\* and made by P800 SRL Via Valdilocchi, 6/F - 19126 La Spezia (SP) - ITALY phone +39.0187300510 - mobile +39.3476400354 commerciale@solareclipse.it P.lva 01353280116







www.solareclipse.it/en \*European patent application EP2989709 - International Patent Application No. PCT/IB2014/060939.






# THE ONLY PATENTED\* STORAGE SYSTEM THAT DOES NOT MODIFY THE INSTALLATION.

# WHY SOLAR ECLIPSE?

#### **NO MODIFY** THE INSTALLATION



#### **EASY AND QUICK TO INSTALL**

Solar Eclipse is the only patented\* storage system for solar panels connected to the grid which **does not require any modifications to the plant**, nor the substitution or installation of a new inverter.

### **ALL POWER AVAILABLE**

Solar Eclipse system is composed of a DC current device and a power meter. You can install **up to 6 DC current devices on the same plant controlled by a single power meter**. Every DC current device can **store from 2 kwh to 14 kwh in one battery pack**. The power meter 6 to 50 kw power and mono-threephases are available. To configure the Solar Eclipse system check the data sheet enclosed.



#### **INFINITE COMPATIBILITY**

Solar Eclipse is **compatible with almost all the grid inverters** available on the market and configurable with all range of the battery pack 48 v: liquid lead, gel lead and lithium\*\*.

\*\* Data exchange with battery packs can be developed.



#### **INTEGRATED REMOTE MONITORING**

"**SolarApp**" allows you to check both photovoltaic and storage system data easily and quickly with one touch.

The app is available for iOS and Android.




DATA SHEET		SOLAR ECLIPSE LIGHT	SOLAR ECLIPSE	SOLAR ECLIPSE Threephases
PV INPUT / GRID	Voltage	150 - 600 V		
INVERTER OUTPUT	Current	17 A		
INPUT / OUTPUT BATTERY PACK	Current	15 A 30 A		
	Voltage	40 - 62 V		
	Storage capacity	2 TO 7,2 kWh 2 TO 14,4 kWh		
POWER METER MONOPHASE 230 V	6 kW X 1	•	•	NO
	6 kW X 2	• •	••	NO
	12 kW X 1	•	•	NO
	12 kW X 2	• •	• •	NO
POWER METER MONOPHASE 400 V	20 kW X 1	• • •	• • •	•
	20 kW X 2	• • • • •		••
	50 kW X 1	• • •	• • •	•
	50 kW X 2	• • • • •		••
PERFORMANCE	Efficiency	98%		
	Stand-By	100 mA - 5 W		
	Temperature	- 20°C / + 50°C		
	Noise	68 db		
	Protection rate	IP 20		
DIMENSIONS AND WEIGHT	Dimensions	34 x 26 x 14 (cm)		
	Weight	6 kg		
CERTIFICATIONS AND WARRANTY		Directive 2006/95/EC Low Voltage directive		
	<i>cc</i>	Directive 2004/108/EC Electromagnetic compatibility directive		
	CE	Directive 2011/65/EC RoHS directive		
		CEI EN62109-1:2010 / CEI EN61000-6-2:2006 / CEI EN61000-6-3:2007 / CEI EN50581:2013		
	V	5 years warranty covers manufactorings defects and any malfuntioning which is not due to incorrect installation or use		

SOLAR ECLIPSE designed, patented and made by P800 SRL Via Valdilocchi, 6/F - 19126 La Spezia (SP) - ITALY phone +39.0187300510 - mobile +39.3476400354 commerciale@solareclipse.it www.solareclipse.it/en - P.Iva 01353280116



#### CONFIGURE YOUR SOUCH ECLIPSE SYSTEM





O3 PV STRING A PV STRING B P

PV STRING C

